PTC Steam Humidifier **Humidasduo**



CE

5-6-19 SANDA-CHO, HACHIOJI, TOKYO 193-0832, JAPAN URL http://www.ucan.co.jp/eng/ E-mail:ucan-information@ucan.co.jp

R UCAN CO., LTD.

HD-M2200



Portable type PTC steam humidifier. Gives hygienical, sterilized and odorless steam humidification suitable for human A/C systems.

Standard Dimensions (mm)







Features

- Mobile with wheel.
- It humidifies room of 320 m³ by just 1 unit.
- Use of high safety, long life PTC immersion heater. Has no cause for concern over fire breaking out even in the waterless operation
- Air cleaning and sterilization function by use of photocatalytic TiO₂ (Titanium dioxide) filter and sterilization lamp.
- Eye-friendly display panel shows various messages.
- Easy, simplified to operate with just one push of a button.
- No piping work needed. Fitted with portable water tanks (10 ℓ tank \times 2). One time filling gives 8 hours continuous humidification.

PTC immersion heater (UCAN's Technology) Has self temperature controlled system which bundles the function of heater and thermostat. It has high-powered output in the water but little current flow in the air by its self-controlled system. Resistivity of heater stays constant to a certain temperature, if the heater temperature rises over it, the resistivity will rise up rapidly (reach Curie point) and control the current flow.

Specifications

-	
Model	Humidasduo HD-M2200
Capacity (Kg/h)	Low:1.2 High: 2.4
Power supply	1Ф2W AC230V (50Hz)
Rated Power (W)	Low:1100 High:2100
Rated Current (A)	Low:4.8 High:9.2
Weight (kg)	Dry : 24.5 Full : 44.5
Air volume	30 mỉ/h
Water quality	Pure water, R.O. treated water (120uS/cm)
Water tank capacity	10ℓ ×2
Humidity setting	1099% RH
Safety features	Electrical leakage sensor
Ambient condition	040 °C (No freezing), Max.70%RH
Safety equipment	Circuit breaker(ELB) to prevent overcurrent, Device to prevent waterless operation
Auxiliary functions	Output switch (L) & (H), Display for current relative humidity (%RH), Function for air cleaning, Function for air sterilization, Fault indications on display
Standard accessories	Water tank (2pcs), Operational and installation manual (1 set)

Applications

Offices
Schools
Public spaces
Hospitals
Beauty salons
Art museums
Electronic component plants, etc