



TURMOCUT LMI 18



Date of issue: 03.08.2017

TURMOCUT LMI 18 is a fully synthetic cutting oil.

TURMOCUT LMI 18 is NSF/H1 approved as lubricant for which incidental contact with food technically cannot be avoided.

Special properties

- Wide temperature range
- Very good surface wetting abilities
- Excellent lubricating properties
- Exceptional penetration capacity of the felt
- Good corrosion protection
- Good wear protection

Product Characteristics	Value	Dimension	Norm / Standard
Colour	clear, transparent		
Density at 20°C	0,82	g/cm ³	DIN 51757
Operating temperature range	-40 to 200	°C	
Oil type	synthetic hydrocarbons		
Kinematic viscosity at 40°C	17	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	3,8	mm ² /s	DIN EN ISO 3104
Viscosity index (VI)	120		DIN ISO 2909
Pour point	-58	°C	DIN ISO 3016
Flash point	> 200	°C	DIN EN ISO 2592

Application

TURMOCUT LMI 18 is used for the lubrication of the cross cutters, the longitudinal cutters and the disc-cut-systems in the paper- and cardboard industry.

Packaging units

6 x 5 l canister, 20 l canister, 60 l drum, 200 l drum



130964



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>