



ELEFANTENMILCH



Date of issue: 08.03.2018

ELEFANTENMILCH (Elephants milk) is a sugar dissolving lubricant ready for application, which preferably finds utilization in the sugar industry.

ELEFANTENMILCH (Elephants milk) is InS/H1 approved as lubricant for which an incidental contact with food technically cannot be avoided.

Special properties

- Easily biodegradable
- Physiologically harmless
- Excellent corrosion protection
- Good adhesive properties
- No separation of the product even with long operating life
- Ideal water soluble
- Dissolving sugar residues

Product Characteristics	Value	Dimension	Norm / Standard
Colour	milky white		
Density at 20°C	0,98	g/cm ³	DIN 51757
Operating temperature range	0 to 65	°C	
pH value	8,5		

Application

Wrapping and packaging machines, pelleting press and foiling machines, rocking levers, joints, spindles, chains, pincers.

ELEFANTENMILCH (Elephants milk) offers a further positive effect. Owing to its high density it penetrates emulsions based on mineral oil and an exchange of lubricants is possible by means of relubrication.

Packaging units

900 ml spray bottle, 1 l bottle, 5 l canister, 10 l canister, 20 l canister, 60 l canister, 200 l drum



1795037



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>