



SINTONO TERRA HLK



Date of issue: 27.01.2016

SINTONO TERRA HLK is a special paste for the lubrication of railheads based on biodegradable synthetic oil.

A combination of selected metallic pigments offers excellent wear-protecting properties to **SINTONO TERRA HLK**.

DB-material No. 991 955

Special properties

- Easily biodegradable
- High pressure resistance
- High ageing resistance
- Good pumpability at low temperature
- Low pour point of the base oil

Product Characteristics	Value	Dimension	Norm / Standard
Colour	silver		
Density at 20°C	1,08	g/cm ³	DIN 51757
Operating temperature range	-40 to 120	°C	
Thickener	Silicate		
Base oil	biodegradable ester		
Kin. viscosity of the base oil at 40°C	46	mm ² /s	DIN EN ISO 3104
Kin. viscosity of the base oil at 100°C	9,2	mm ² /s	DIN EN ISO 3104
Unworked penetration	400 – 430	mm/10	DIN ISO 2137
Consistency class (NLGI)	00		DIN 51818
Biodegradability after 28 days	> 70	%	OECD 301

Packaging units

20 x 400 g cartridges, 6 x 1 kg cans, 5 kg bucket, 10 kg hobbock, 25 kg hobbock, 50 kg hobbock, 180 kg drum