



Plate & Shell Heat Exchangers



Refrigeration

Vahterus Plate & Shell Heat Exchangers (PSHE) have many benefits for advanced refrigeration applications such as evaporators, condensers, cascades, desuperheaters and oil coolers.

PSHE are effective, durable and versatile due to their unique shell

construction, together with fully welded plates. This makes PSHE ideal, also for contractors who need compact size and low refrigerant charge. Vahterus Heat Exchangers are suitable for all refrigerants, especially natural media such as ammonia and carbon dioxide.

Main Applications

Evaporators

The versatility of Vahterus PSHE is demonstrated particularly in evaporator applications. PSHE can be used as highly efficient Flooded, or Direct Expansion (DX) evaporators, due to low pressure drop and high heat transfer. Fully welded circular plates and a protective outer shell, guarantees safety for the end user. This construction also ensures high integrity and durability.

Flooded Evaporators

- Refrigerants: NH₃, CO₂, R404, R134a, propane, methane, etc.
- Capacity Range: 5 - 20 000 kW
- Compact Size & Small Refrigerant Charge
- Low Evaporative Side Pressure Drop
- Flexible Construction
- High Efficiency
- Safe Operation

Direct Expansion (DX) Evaporators

- Capacity Range: 5 - 1 500 kW
- Can Be Used For All Refrigerants
- Compact Size
- Safe Operation

Cascades

Cascade heat exchangers are used to transfer heat between two refrigerants. They are used especially with CO₂. A cascade unit combines both condenser and evaporator (flooded or DX).

Vahterus PSHE are ideal for cascade operations, based on their high thermal efficiency. They can provide minimum temperature difference between the evaporative and condensing media, and low running costs. Using Vahterus fully welded construction ensures there is no leakage or cross-contamination.

- Refrigerants: NH₃, CO₂, R404, R134a, propane, methane, etc.
- Capacity Range: 5 - 10 000 kW
- Compact Size & Small Refrigerant Charge
- High Heat Transfer
- Low Pressure Drop
- Many Materials Available
- Easy to Install and Insulate

Vahterus Systems, Flooded Evaporators + Droplet Separators

- Capacity Range: 100 - 5 000 kW
- Compact Size & Small Refrigerant Charge
- Possibility for Internal and External Circulation Systems
- Flexible and z i.e. Customised Construction
- Safe Operation
- Ready to be Installed

Combined

Combined is a new, extremely compact solution for flooded evaporators and flooded cascades. The evaporator, or cascade, and surge drum are all in one shell. Combined is especially suitable for limited spaces, such as marine applications or production facilities with very limited height. In addition to the compact size, it creates cost savings with insulation, piping and amount of refrigerant needed.

- Flooded Evaporators + Separator
- Flooded Cascade + Separator
- Multi Pass Droplet Separation
- Capacity Range: 50 - 20 000 kW
- Small Refrigerant Charge
- Round Plate

Condensers

The construction of Vahterus PSHE is ideal for condensing applications. Key benefits include high thermal efficiency, small/reduced refrigerant charge, and low pressure drop. PSHE are suitable for all refrigerants over a wide temperature and capacity range.

- Refrigerants: NH₃, CO₂, R404, R134a, propane, methane, etc.
- Capacity Range: 5 - 10 000 kW
- Compact Size & Small Refrigerant Charge
- High Heat Transfer
- Low Pressure Drop
- Many Materials Available
- Easy to Install and Insulate

Other Applications

Desuperheaters



Oil Coolers



Ammonia Absorption Plant





Vahterus provides solutions for many heat transfer needs. We have considerable experience with heat transfer technology and continually invest in Research & Development.

High quality, consistent and reliable products are a matter of principle to us.

Compact & Effective

Vahterus PSHE combines the benefits of Plate & Frame and Shell & Tube heat exchangers. PSHE can either be described as a fully welded, high integrity plate heat exchanger, with no gaskets; or a generic alternative to Shell & Tube, approx. 25% of the footprint, displaying both space and weight benefits.

Benefits of PSHE

- No Gaskets or Brazing
- High Integrity / Total Containment
- Strong and Safe Construction
- Unique Protection and Resistance to Thermal and Pressure Cycling
- Thermally Efficient
- Compact and Low Weight
- Flexible Construction
- Proven, Reliable Technology
- Low Fouling
- Minimal Maintenance Requirement
- Close Approach Temperatures



Technical Specification

Maximum Heat Transfer Area

- 2 000 m²/exchanger

Mechanical Design

- Full vacuum to 150 bar possible
- -164 to +899°C

Quality Systems:

- ISO 9001:2000
- EN ISO 3834-2
- PED Module B+D
- ASME U Stamp
- OHSAS 18001
- ISO 14001



Approvals:

- | | |
|--------------------------|-------------------|
| • PED | • R.I.N.A |
| • ASME U Stamp & R Stamp | • ABS Europe Ltd. |
| • SELO, China | • Bureau Veritas |
| • AD-2000 HPO | • DNV |
| • Germanischer Lloyd | • MKE South Korea |
| • Lloyd's Register | |

Materials:

Shell:	Plates:
• AISI 316	• AISI 316L
• St 35.8/1 / P235GH	• Titanium, Grade 1
• P265GH	• C22
• P355NL2	• C276
• EN 1.4547, SMO254	• Nickel 201
• EN 1.4539, 904L	• EN 1.4547, SMO254
	• EN 1.4539, 904L
	• EN 1.4462, Duplex
	• other materials on request

Main Data:

	Area/plate, m ²	Plate side nozzles, DN	Shell side nozzles, DN
PSHE 2	0.032	25	20-80
PSHE 3	0.076	50	25-250
PSHE 4	0.15	80	25-300
PSHE 5	0.26	100	25-350
PSHE 6	0.35	125	25-500
PSHE 7	0.46	150	25-500
PSHE 9	0.80	200	25-700
PSHE 14	1.55	300	25-1000
PRHE 12	1.00	200	25-1000



Vahterus Oy

Pruukintie 7
FI-23600 Kalanti
FINLAND
Tel. +358 2 840 70
Fax +358 2 840 7299
sales@vahterus.com

Vahterus Americas, LLC

PO Box 77264
Charlotte
NC 28271
USA
Tel. +1 704 846 5050
sales.americas@vahterus.com

Vahterus Deutschland GmbH

Magnolienweg 26
63741 Aschaffenburg
GERMANY
Tel. +49 6021 181 700
webmaster@vahterus.de

Vahterus Heat Exchangers

Shanghai Co., Ltd
Room 816, Enterprise Square
Mei Yuan Road 228,
Zha Bei District
200070 Shanghai
CHINA

Tel. +86 21 638 00848 *113
sales_china@vahterus.com

Vahterus (UK) Ltd

12-14 Derby Road, Melbourne
Derbyshire DE73 8FE
UK

Tel. +44 1332 863175
vahterus.uk@vahterus.com

